

Meet the Wyse Intel-based 3000 series thin client

More organizations than ever before are now moving to desktop virtualization to improve security, ease ongoing desktop management and maintenance, and lower ongoing costs. To help achieve these benefits, Dell offers the Wyse Intel-based 3000 series thin client.

Big Performance

While small in size, this Windows Embedded Standard 7 (WES7) thin client packs plenty of punch. Powered by a dual core Intel Celeron processor, it's more than capable of driving a wide range of applications, including HD multimedia and rich graphics, to just about all of your task workers and knowledge workers. In fact, it offers over four times the processing power and twice the graphics rendering capability of its Wyse predecessor thin client.

Broad Application Support

This Intel-based x86 embedded thin client runs WES7 locally to support all of your Windows apps via virtual desktop connection, locally on the device, or via a VPN. So you can support your entire existing app mix while you move your people to virtual desktops.

Highly Configurable

What truly sets this thin client apart from others is how well-connected it is. With a choice of five back panel networking and peripheral interface choices, you can support a broad mix of network connections and device attachments. It's the thin client that can be configured for your entire organization.

Outstanding reliability

With no moving parts and built to last, the Wyse Intel-based 3000 series thin client will offer many years of high-performance service, which keeps your people and your IT and finance teams happy.

With Wyse thin clients, customers get a complete services portfolio including Deployment Services, ProSupport and Accidental Damage service, giving Dell business partners end-to-end support throughout the product lifecycle.

Specifications Dell Wyse 3030 thin client Windows Embedded Standard 7 Operating system **CPU** Intel Celeron N2807 1.6 GHz dual core processor Memory 16GB Flash / 4GB RAM DDR3 Graphics Embedded 1 x DVI-I port 1 x DVI-D port I/O peripheral support 1 x SuperSpeed USB 3.0 port on the front (backwards-compatible with USB 2.0) 3 x USB 2.0 ports (1 front, 2 back) Optional serial port 10/100/1000 Gigabit Ethernet Networking Optional dual band 802.11 a/b/g/n/ac wireless Optional SFP Module support for Fiber NIC network connectivity VESA monitor support with Display Data Control (DDC) for automatic setting Resolution of resolution and refresh rate Single and dual display: 1920 x 1200 at 32bpp **Audio** Composite audio jack: 1/8-inch mini, 16-bit stereo / Internal mono speaker Without stand: 7.37 in x 1.15 in x 4.61 in (187mm x 29mm x 117mm) **Dimensions** With stand: 7.78 in x 1.15 in x 4.61 in (197.5mm x 69mm x 117mm) Shipping weight 5.3 lbs. (2.34 kg) Vertical feet, standard Optional VESA mounting bracket for mounting to flat surfaces, such as walls Mountings Please note: 5000 series clients cannot mount directly to the backs of monitors Optional Ergotron mounting stand for mounting with Dell monitors **Device security** Built-in Kensington security slot (cable sold separately) Worldwide auto-sensing 100-240 VAC, 50/60 Hz 65W, 19V DC Energy Star V.5.2 Phase V external and EuP compliant power adapter **Power** Consumes less than 6 watts (average) Operating, vertical position: 32° to 104° F (10° to 40° C) Temperature range Storage: 14° to 140° F (-10° to 60° C) 20% to 80% condensing. 10% to 95% non-condensing Humidity Ergonomics: German EKI-ITB 2000, ISO 9241-3/-8 Safety: cULus 60950, TÜV-GS, EN 60950 Safety certifications RF Interference: FCC Class B, CE, VCCI, C-Tick Environmental: WEEE, RoHS Compliant Warranty Three-year hardware warranty Support and deployment Complete services portfolio including Deployment Services, ProSupport and Accidental Damage service.

Learn more: Visit www.dell.com/wyse

Dell Inc. One Dell Way Round Rock, TX 78664 Visit our website at: www.dell.com/wyse

Ask a Dell expert:

https://marketing.dell.com/t2d-wyse

Dell cloud client-computing sales 1-800-438-9973 CCC_sales@dell.com